

30x 30 x 10 mm Series

Dimensions



Specifications

Model	Rated Voltage (VDC)	Rated Current (Amp)	Input Power (Watts)	Nominal Speed (RPM)	Airflow (CFM)	Static Pressure (mm-H ₂ O)	Noise Level (dBA)
SA31S5L	5	0.14	0.70	7000	2.76	1.78	20.9
SA31S5M	5	0.16	0.80	8000	3.11	2.33	23.8
SA31S5H	5	0.18	0.90	9000	3.59	2.95	26.4
SA31S2L	12	0.07	0.84	7000	2.77	1.78	20.9
SA31S2M	12	0.08	0.96	8000	3.17	2.33	23.8
SA31S2H	12	0.09	1.08	9000	3.56	2.95	26.4
SA31S2U	12	0.10	1.2	10000	3.94	3.64	28.7
SA31S4L	24	0.04	0.96	7000	2.76	1.78	20.9
SA31S4M	24	0.05	1.2	8000	3.11	2.33	23.8
SA31S4H	24	0.06	1.44	9000	3.59	2.95	26.4

Bearing Type

Sleeve	1-Ball-1-Sleeve	2-Ball
◎	◎	◎

Safety Approvals

UL	TUV	CSA	CE
◎	◎	◎	◎

